



KARTA KATALOGOWA

ZASILACZE LED PRĄDOWE



VS LIGHTING SOLUTIONS

Input voltage 220-240 VAC

100mA
800mA



NOT
DIMM

SELV

RESISTOR
excl.



| No. Art. | Name | Type | Output voltage | Max. output W | Output current | Length (mm) | Width (mm) | Height (mm) |
|----------|---|----------------------------------|----------------|---------------|----------------|-------------|------------|-------------|
| 186585 | ECXe 400.223 Standard/ Selectable Current - resistor | constant current driver/internal | 30-120 VDC | 40W | 100-400mA | 280mm | 30mm | 21mm |
| 186586 | ECXe 800.224 Standard/ Selectable Current - resistor | constant current driver/internal | 30-70 VDC | 40W | 400-800mA | 280mm | 30mm | 21mm |
| 186587 | ECXe 400.225 Standard/ Selectable Current - resistor | constant current driver/internal | 100-225 VDC | 85W | 100-400mA | 280mm | 30mm | 21mm |
| 186588 | ECXe 800.226 Standard/ Selectable Current - resistor | constant current driver/internal | 30-130 VDC | 85W | 400-800mA | 280mm | 30mm | 21mm |
| 186695 | ECXe 800.262 Standard/ Selectable Current - resistor | constant current driver/internal | 88-280 VDC | 120W | 400-800mA | 280mm | 30mm | 21mm |
| 186696 | ECXe 800.263 Standard/ Selectable Current - resistor | constant current driver/internal | 120-360 VDC | 165W | 400-800mA | 359mm | 30mm | 21mm |



WYBÓR REZYSTORÓW LED/CHOICE of LEDset Resistor

| Resistors | | ECXe 400.223 | | | | ECXe 400.225 | | | |
|-------------------------|----------------|-------------------------|--------|----------------------------|--------|-------------------------|--------|----------------------------|--------|
| Nominal current I rated | Resistor kΩ | LED output Voltage ULED | | Led nominal output P rated | | LED output Voltage ULED | | Led nominal output P rated | |
| | | V min. | V max. | W min. | W max. | V min. | V max. | W min. | W max. |
| 100 | 50.00 | 30 | 120 | 3.00 | 12 | 100 | 225 | 10.00 | 22.50 |
| 125 | 40.00 | 30 | 120 | 3.75 | 15 | 100 | 225 | 12.50 | 28.10 |
| 150 | 33.33 | 30 | 120 | 4.50 | 18 | 100 | 225 | 15.00 | 33.75 |
| 175 | 28.57 | 30 | 120 | 5.25 | 21 | 100 | 225 | 17.50 | 39.40 |
| 200 | 25.00 | 30 | 120 | 6.00 | 24 | 100 | 225 | 20.00 | 45.00 |
| 225 | 22.22 | 30 | 120 | 6.75 | 27 | 100 | 225 | 22.50 | 50.60 |
| 250 | 20.00 | 30 | 120 | 7.50 | 30 | 100 | 225 | 25.00 | 56.25 |
| 275 | 18.18 | 30 | 120 | 8.25 | 33 | 100 | 225 | 27.50 | 61.90 |
| 300 | 16.67 | 30 | 120 | 9.00 | 36 | 100 | 225 | 30.00 | 67.50 |
| 325 | 15.39 | 30 | 120 | 9.75 | 39 | 100 | 225 | 32.50 | 73.10 |
| 350 | 14.29 | 30 | 114 | 10.50 | 40 | 100 | 225 | 35.00 | 78.75 |
| 375 | 13.33 | 30 | 107 | 11.25 | 40 | 100 | 223 | 37.50 | 83.00 |
| 400 | 12.50 | 30 | 100 | 12.00 | 40 | 100 | 212 | 40.00 | 85.00 |
| Resistors | | ECXe 800.224 | | | | ECXe 800.226 | | | |
| 400 | 12.50 | 30 | 70 | 12.00 | 28.00 | 30 | 130 | 12.00 | 52.00 |
| 425 | 11.76 | 30 | 70 | 12.75 | 29.75 | 30 | 130 | 12.75 | 55.25 |
| 450 | 11.11 | 30 | 70 | 13.50 | 31.50 | 30 | 130 | 13.50 | 58.50 |
| 475 | 10.53 | 30 | 70 | 14.25 | 33.25 | 30 | 130 | 14.25 | 61.75 |
| 500 | 10.00 | 30 | 70 | 15.00 | 35.00 | 30 | 130 | 15.00 | 65.00 |
| 525 | 9.52 | 30 | 70 | 15.75 | 36.75 | 30 | 130 | 15.75 | 68.25 |
| 550 | 9.09 | 30 | 70 | 16.50 | 38.50 | 30 | 130 | 16.50 | 71.50 |
| 575 | 8.70 | 30 | 69.60 | 17.25 | 40.00 | 30 | 130 | 17.25 | 74.75 |
| 600 | 8.33 | 30 | 66.70 | 18.00 | 40.00 | 30 | 130 | 18.00 | 78.00 |
| 625 | 8.00 | 30 | 64.00 | 18.75 | 40.00 | 30 | 130 | 18.75 | 81.25 |
| 650 | 7.69 | 30 | 61.50 | 19.50 | 40.00 | 30 | 130 | 19.50 | 84.50 |
| 675 | 7.41 | 30 | 59.30 | 20.25 | 40.00 | 30 | 126 | 20.25 | 85.00 |
| 700 | 7.14 | 30 | 57.10 | 21.00 | 40.00 | 30 | 121 | 21.00 | 85.00 |
| 725 | 6.90 | 30 | 55.20 | 21.75 | 40.00 | 30 | 117 | 21.75 | 85.00 |
| 750 | 6.67 | 30 | 53.30 | 22.50 | 40.00 | 30 | 113 | 22.50 | 85.00 |
| 775 | 6.45 | 30 | 51.60 | 23.25 | 40.00 | 30 | 109 | 23.25 | 85.00 |
| 800 | 6.25 | 30 | 50.00 | 24.00 | 40.00 | 30 | 106 | 24.00 | 85.00 |
| Resistors | | ECXe 800.262 | | | | ECXe 800.263 | | | |
| Nominal current I rated | Resistor kΩ | LED output Voltage ULED | | Led nominal output P rated | | LED output Voltage ULED | | Led nominal output P rated | |
| | | V min. | V max. | W min. | W max. | V min. | V max. | W min. | W max. |
| 400 | 12.50 | 175 | 280 | 70 | 112 | 238 | 360 | 95 | 144 |
| 425 | 11.76 | 165 | 280 | 70 | 119 | 224 | 360 | 95 | 153 |
| 450 | 11.11 | 156 | 267 | 70 | 120 | 211 | 360 | 95 | 162 |
| 475 | 10.53 | 147 | 253 | 70 | 120 | 200 | 347 | 95 | 165 |
| 500 | 10.00 | 140 | 240 | 70 | 120 | 190 | 330 | 95 | 165 |
| 525 | 9.52 | 133 | 229 | 70 | 120 | 191 | 314 | 95 | 165 |
| 550 | 9.09 | 127 | 218 | 70 | 120 | 173 | 300 | 95 | 165 |
| 575 | 8.70 | 122 | 209 | 70 | 120 | 165 | 287 | 95 | 165 |
| 600 | 8.33 | 117 | 200 | 70 | 120 | 158 | 275 | 95 | 165 |
| 625 | 8.00 | 112 | 192 | 70 | 120 | 152 | 264 | 95 | 165 |
| 650 | 7.69 | 108 | 185 | 70 | 120 | 146 | 254 | 95 | 165 |
| 675 | 7.41 | 104 | 178 | 70 | 120 | 141 | 244 | 95 | 165 |
| 700 | 7.14 | 100 | 171 | 70 | 120 | 136 | 236 | 95 | 165 |
| 725 | 6.90 | 97 | 166 | 70 | 120 | 131 | 228 | 95 | 165 |
| 750 | 6.67 | 93 | 160 | 70 | 120 | 127 | 220 | 95 | 165 |
| 775 | 6.45 | 90 | 155 | 70 | 120 | 123 | 213 | 95 | 165 |
| 800 | 6.25 | 88 | 150 | 70 | 120 | 120 | 206 | 95 | 165 |