



## KARTA KATALOGOWA

### ZASILACZE LED PRĄDOWE



Input voltage 220-240 VAC

VS LIGHTING SOLUTIONS

No. Art.	Name	Type	Output voltage	Max. output W	Output current	Length (mm)	Width (mm)	Height (mm)
186650	ECXe 900.241 Standard/ Selectable Current - resistor	constant current driver/internal	25-43 VDC	39W	150-900mA	97mm	43mm	30mm
186664	ECXe 1050.251 Standard/	constant current driver/internal	25-43 VDC	45W	150-1050mA	97mm	43mm	30mm

#### WYBÓR REZYSTORÓW LED / CHOICE of LEDset Resistor

Resistors		ECXe 900.241				ECXe 1050.251			
Nominal current I rated	Resistor	LED output Voltage ULED		Led nominal output P rated		LED output Voltage ULED		Led nominal output P rated	
mA	kΩ	V min.	V max.	W min.	W max.	V min.	V max.	W min.	W max.
150	33.33	25	43	3.75	6.45	25	43	3.75	6.45
175	28.57	25	43	4.38	7.53	25	43	4.38	7.53
200	25.00	25	43	5.00	8.60	25	43	5.00	8.60
225	22.22	25	43	5.63	9.68	25	43	5.63	9.68
250	20.00	25	43	6.25	10.75	25	43	6.25	10.75
275	18.18	25	43	6.88	11.83	25	43	6.88	11.83
300	16.67	25	43	7.50	12.90	25	43	7.50	12.90
325	15.39	25	43	8.13	13.98	25	43	8.13	13.98
350	14.29	25	43	8.75	15.05	25	43	8.75	15.05
375	13.33	25	43	9.38	16.13	25	43	9.38	16.13
400	12.50	25	43	10.00	17.20	25	43	10.00	17.20
425	11.76	25	43	10.63	18.28	25	43	10.63	18.28
450	11.11	25	43	11.25	19.35	25	43	11.25	19.35
475	10.53	25	43	11.88	20.43	25	43	11.88	20.43
500	10.00	25	43	12.50	21.50	25	43	12.50	21.50
525	9.52	25	43	13.13	22.58	25	43	13.13	22.58
550	9.09	25	43	13.75	23.65	25	43	13.75	23.65
575	8.70	25	43	13.38	24.73	25	43	13.38	24.73
600	8.33	25	43	15.00	25.80	25	43	15.00	25.80
625	8.00	25	43	16.63	26.88	25	43	16.63	26.88
650	7.69	25	43	16.25	27.95	25	43	16.25	27.95
675	7.41	25	43	16.88	29.03	25	43	16.88	29.03
700	7.14	25	43	17.50	30.10	25	43	17.50	30.10
725	6.90	25	43	18.13	31.18	25	43	18.13	31.18
750	6.67	25	43	18.75	32.25	25	43	18.75	32.25
775	6.45	25	43	19.38	33.33	25	43	19.38	33.33
800	6.25	25	43	20.00	34.40	25	43	20.00	34.40
825	6.06	25	43	20.63	35.48	25	43	20.63	35.48
850	5.88	25	43	21.25	36.55	25	43	21.25	36.55
875	5.71	25	43	21.88	37.63	25	43	21.88	37.63
900	5.56	25	43	22.50	38.70	25	43	22.50	38.70
925	5.41	-	-	-	-	25	43	23.13	39.78
950	5.26	-	-	-	-	25	43	23.75	40.85
975	5.13	-	-	-	-	25	43	24.38	41.93
1000	5.00	-	-	-	-	25	43	25.00	43.00
1025	4.88	-	-	-	-	25	43	25.63	44.08
1050	4.76	-	-	-	-	25	43	26.25	45.15