



KARTA KATALOGOWA

ZASILACZE LED PRĄDOWE



VS LIGHTING SOLUTIONS

Input voltage 220–240 VAC

300mA
1050mA



DALI
DIMM

SELV



No. Art.	Name	Type	Output voltage	Max. output W	Output current	Length (mm)	Width (mm)	Height (mm)
186762	ECXd 1050.299 Dimmable DALI/Selectable Current	constant current driver/internal	10-54 VDC	16W	300mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	18W	350mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	21W	400mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	24W	450mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	27W	500mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	29W	550mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	32W	600mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	35W	650mA	97.2mm	43.2mm	30.1mm
			10-54 VDC	38W	700mA	97.2mm	43.2mm	30.1mm
			10-51 VDC	38W	750mA	97.2mm	43.2mm	30.1mm
			10-48 VDC	38W	800mA	97.2mm	43.2mm	30.1mm
			10-45VDC	38W	850mA	97.2mm	43.2mm	30.1mm
			10-43 VDC	38W	900mA	97.2mm	43.2mm	30.1mm
			10-40 VDC	38W	950mA	97.2mm	43.2mm	30.1mm
			10-38 VDC	38W	1000mA	97.2mm	43.2mm	30.1mm
10-36 VDC	38W	1050mA	97.2mm	43.2mm	30.1mm			
186763*	ECXd 1050.299 Dimmable DALI/Selectable Current	constant current driver/internal	*Dane techniczne jak art. 186762, wymiary: 146.5mm x 43.2mm x 30.1mm / Technical details same as 186762, dimensions: 146.5 x 43.2 x 30.1mm					